SAFETY DATA SHEET

Issuing Date 20-Jul-2021 **Revision Date** 10-Nov-2020 **Revision Number** 1

NGHS / English

The supplier identified below generated this SDS using the UL SDS template. UL did not test, certify, or approve the substance described in this SDS, and all information in this SDS was provided by the supplier or was reproduced from publically available regulatory data sources. UL makes no representations or warranties regarding the completeness or accuracy of the information in this SDS and disclaims all liability in connection with the use of this information or the substance described in this SDS. The layout, appearance and format of this SDS is © 2014 UL LLC. All rights reserved.

1. IDENTIFICATION

Product identifier

Product Name GERM-X

Other means of identification

Product Code(s) 1515573_HD

Recommended use of the chemical and restrictions on use

Recommended Use Hand sanitizer - Liquid

Restrictions on use No information available

Details of the supplier of the safety data sheet

Supplier Identification Vi-Jon Inc.

Address
8515 Page Avenue
Saint Louis
MO
63114
US

Telephone
Phone:3144271000
Fax:3144271010

E-mail jstilts@vijon.com

Emergency telephone number

Company Emergency Phone Number 18004249300

2. HAZARDS IDENTIFICATION

Classification

Flammable liquids	Category 2

Appearance Clear **Physical state** Viscous liquid Liquid **Odor** Alcohol

GHS Label elements, including precautionary statements

Danger

Hazard statements
Highly flammable liquid and vapor



Precautionary Statements - Prevention
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
Keep container tightly closed
Ground/bond container and receiving equipment
Use explosion-proof electrical/ ventilating/ lighting/ equipment
Use only non-sparking tools
Take precautionary measures against static discharge
Wear protective gloves/eye protection/face protection
Precautionary Statements - Response

Skin
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
Fire
In case of fire: Use CO2, dry chemical, or foam to extinguish

Precautionary Statements - Storage
Store in a well-ventilated place. Keep cool

Precautionary Statements - Disposal
Dispose of contents/container to an approved waste disposal plant

Other information
Toxic to aquatic life.

Unknown acute toxicity 54.52788 % of the mixture consists of ingredient(s) of unknown toxicity
0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
54.52788 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
54.52788 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
54.52788 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not applicable.

Mixture

Chemical name	CAS No	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Ethyl alcohol	64-17-5	54.52788	-	-
Water, distilled, conductivity or of similar purity	7732-18-5	44.53478	-	-
Glycerin	56-81-5	0.4975	-	-
Carbomer	9003-01-4	0.18705	-	-
Acrylates/C10-30 Alkyl Acrylate Crosspolymer	NA390	0.15	-	-
Diisopropylamine	108-18-9	0.095221	-	-
tert-Butyl alcohol	75-65-0	0.07088	-	-
Isopropyl myristate	110-27-0	0.05	-	-
Fragrance (Irritating to eyes)	FRAGRANCE	0.035	-	-
Tocopheryl acetate	7695-91-2	0.001	-	-
Denatonium benzoate	3734-33-6	0.000407	-	-
Isopropylamine	75-31-0	0.000096	-	-
Isopropyl alcohol	67-63-0	0.000096	-	-
Acetone	67-64-1	0.000096	-	-

4. FIRST AID MEASURES

Description of first aid measures

Inhalation Remove to fresh air.

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Keep eye wide open while rinsing. Do not rub affected area.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.

Ingestion Clean mouth with water and drink afterwards plenty of water.

Self-protection of the first aider Remove all sources of ignition. Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination. Use personal protective equipment as required. See section 8 for more information.

Most important symptoms and effects, both acute and delayed

Symptoms No information available.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Dry chemical. Carbon dioxide (CO2). Water spray. Alcohol resistant foam.

Large Fire	CAUTION: Use of water spray when fighting fire may be inefficient.
Unsuitable extinguishing media	Do not scatter spilled material with high pressure water streams.
Specific hazards arising from the chemical	Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Hazardous Combustion Products	Carbon oxides.
Explosion Data	
Sensitivity to Mechanical Impact	None.
Sensitivity to Static Discharge	Yes.
Special protective equipment for fire-fighters	Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal precautions	Evacuate personnel to safe areas. Use personal protective equipment as required. See section 8 for more information. Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Keep people away from and upwind of spill/leak. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled material.
Other Information	Ventilate the area.

Methods and material for containment and cleaning up

Methods for containment	Stop leak if you can do it without risk. Do not touch or walk through spilled material. A vapor suppressing foam may be used to reduce vapors. Dike far ahead of spill to collect runoff water. Keep out of drains, sewers, ditches and waterways. Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal.
Methods for cleaning up	Take precautionary measures against static discharges. Dam up. Soak up with inert absorbent material. Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on safe handling	Use personal protection equipment. Avoid contact with skin and eyes. Avoid breathing vapors or mists. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use with local exhaust ventilation. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage Conditions	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static

electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

Exposure Limits .

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Ethyl alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m³ (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m³	IDLH: 3300 ppm 10% LEL TWA: 1000 ppm TWA: 1900 mg/m³
Glycerin 56-81-5	TWA: 10 mg/m³ mist	TWA: 15 mg/m³ mist, total particulate TWA: 5 mg/m³ mist, respirable fraction (vacated) TWA: 10 mg/m³ mist, total particulate (vacated) TWA: 5 mg/m³ mist, respirable fraction	
Diisopropylamine 108-18-9	TWA: 5 ppm S*	TWA: 5 ppm TWA: 20 mg/m³ (vacated) TWA: 5 ppm (vacated) TWA: 20 mg/m³ (vacated) S* S*	IDLH: 200 ppm TWA: 5 ppm TWA: 20 mg/m³
tert-Butyl alcohol 75-65-0	TWA: 100 ppm	TWA: 100 ppm TWA: 300 mg/m³ (vacated) TWA: 100 ppm (vacated) TWA: 300 mg/m³ (vacated) STEL: 150 ppm (vacated) STEL: 450 mg/m³	IDLH: 1600 ppm TWA: 100 ppm TWA: 300 mg/m³ STEL: 150 ppm STEL: 450 mg/m³
Isopropylamine 75-31-0	STEL: 5 ppm TWA: 2 ppm S*	TWA: 5 ppm TWA: 12 mg/m³ (vacated) TWA: 5 ppm (vacated) TWA: 12 mg/m³ (vacated) STEL: 10 ppm (vacated) STEL: 24 mg/m³	IDLH: 750 ppm
Isopropyl alcohol 67-63-0	STEL: 400 ppm TWA: 200 ppm	TWA: 400 ppm TWA: 980 mg/m³ (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m³ (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m³	IDLH: 2000 ppm 10% LEL TWA: 980 mg/m³ TWA: 400 ppm STEL: 500 ppm STEL: 1225 mg/m³
Acetone 67-64-1	STEL = 750 ppm TWA: 500 ppm	TWA: 1000 ppm TWA: 2400 mg/m³ (vacated) TWA: 1800 mg/m³ (vacated) TWA: 750 ppm (vacated) STEL: 1000 ppm (vacated) STEL: 2400 mg/m³	IDLH: 2500 ppm 10% LEL TWA: 250 ppm TWA: 590 mg/m³

Chemical name	Alberta	British Columbia	Ontario TWAEV	Quebec
Ethyl alcohol 64-17-5	TWA: 1000 ppm TWA: 1880 mg/m³	STEL: 1000 ppm	STEL: 1000 ppm	STEL: 1000 ppm

Glycerin 56-81-5	TWA: 10 mg/m³	TWA: 10 mg/m³ TWA: 3 mg/m³		TWA: 10 mg/m³
Diisopropylamine 108-18-9	TWA: 5 ppm TWA: 21 mg/m³ Skin	TWA: 5 ppm Skin	TWA: 5 ppm Skin	TWA: 5 ppm TWA: 21 mg/m³ Skin
tert-Butyl alcohol 75-65-0	TWA: 100 ppm TWA: 303 mg/m³	TWA: 100 ppm	TWA: 100 ppm	TWA: 100 ppm TWA: 303 mg/m³
Isopropylamine 75-31-0	TWA: 5 ppm TWA: 12 mg/m³ STEL: 10 ppm STEL: 24 mg/m³	TWA: 5 ppm STEL: 10 ppm	TWA: 5 ppm STEL: 10 ppm	TWA: 5 ppm TWA: 12 mg/m³ STEL: 10 ppm STEL: 24 mg/m³
Isopropyl alcohol 67-63-0	TWA: 200 ppm TWA: 492 mg/m³ STEL: 400 ppm STEL: 984 mg/m³	TWA: 200 ppm STEL: 400 ppm	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 985 mg/m³ STEL: 500 ppm STEL: 1230 mg/m³
Acetone 67-64-1	TWA: 500 ppm TWA: 1200 mg/m³ STEL: 750 ppm STEL: 1800 mg/m³	TWA: 250 ppm STEL: 500 ppm	TWA: 250 ppm STEL: 500 ppm	TWA: 500 ppm TWA: 1190 mg/m³ STEL: 1000 ppm STEL: 2380 mg/m³

Other Exposure Guidelines Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992). See section 15 for national exposure control parameters.

Appropriate engineering controls

Engineering controls Showers
Eyewash stations
Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection Tight sealing safety goggles.

Hand protection Wear suitable gloves. Impervious gloves.

Skin and body protection Wear suitable protective clothing. Long sleeved clothing. Chemical resistant apron. Antistatic boots.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice. Do not eat, drink or smoke when using this product. Contaminated work clothing should not be allowed out of the workplace. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state Viscous liquid; Liquid
Appearance Clear
Odor Alcohol
Color No information available
Odor Threshold No data available

Property	Values	Remarks Method
pH	7.0	
Melting / freezing point	No data available	None known

Boiling point / boiling range	No data available	None known
Flash Point	22 C / 72 F	
Evaporation Rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability limit	No data available	
Lower flammability limit	No data available	
Vapor pressure	No data available	None known
Vapor density	No data available	None known
Relative density	0.9	
Water Solubility	Miscible in water	
Solubility(ies)	No data available	None known
Partition coefficient: n-octanol/water	0	
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known
Dynamic viscosity	No data available	None known

Other Information

Explosive properties	No information available
Oxidizing properties	No information available
Softening Point	No information available
Molecular Weight	No information available
VOC Content (%)	No information available
Liquid Density	No information available
Bulk Density	No information available
Particle Size	No information available
Particle Size Distribution	No information available

10. STABILITY AND REACTIVITY

Reactivity No information available.

Chemical stability Stable under normal conditions.

Possibility of Hazardous Reactions None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to avoid Heat, flames and sparks.

Incompatible materials None known based on information supplied.

Hazardous Decomposition Products Carbon oxides.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Inhalation Specific test data for the substance or mixture is not available.

Eye contact Specific test data for the substance or mixture is not available.

Skin contact Specific test data for the substance or mixture is not available.

Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms No information available.

Numerical measures of toxicity

Acute toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

ATEmix (oral) 12,947.50 mg/kg
ATEmix (inhalation-dust/mist) 228.70 mg/L

Unknown acute toxicity 54.52788 % of the mixture consists of ingredient(s) of unknown toxicity
0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity
54.52788 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity
54.52788 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas)
54.52788 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor)
0 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist)

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl alcohol	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
Water, distilled, conductivity or of similar purity	> 90 mL/kg (Rat)	-	-
Glycerin	= 12600 mg/kg (Rat)	> 10 g/kg (Rabbit)	> 2.75 mg/L (Rat) 4 h
Carbomer	= 2500 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 5.1 mg/L (Rat) 4 h
Diisopropylamine	= 770 mg/kg (Rat)	= 2000 mg/kg (Rabbit)	= 5.35 mg/L (Rat) 4 h
tert-Butyl alcohol	= 2200 mg/kg (Rat)	> 2 g/kg (Rabbit)	> 10000 ppm (Rat) 4 h
Isopropyl myristate	> 10000 mg/kg (Rat)	= 5 g/kg (Rabbit)	> 41 mg/L (Rat) 1 h
Tocopheryl acetate	-	> 3000 mg/kg (Rat)	-
Denatonium benzoate	= 584 mg/kg (Rat)	> 2000 mg/kg (Rat)	= 0.2 mg/L (Rat) 4 h
Isopropylamine	= 111 mg/kg (Rat)	= 382 mg/kg (Rat)	= 8.7 mg/L (Rat) 4 h
Isopropyl alcohol	= 1870 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	> 10000 ppm (Rat) 6 h
Acetone	= 5800 mg/kg (Rat)	> 15700 mg/kg (Rabbit)	= 50100 mg/m³ (Rat) 8 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity Ethanol has been shown to be carcinogenic in long-term studies only when consumed as alcoholic beverage.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethyl alcohol 64-17-5	A3	Group 1	Known	X
Carbomer 9003-01-4	-	Group 3	-	-

Isopropyl alcohol 67-63-0	-	Group 3	-	X

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to Humans
Group 3 - Not Classifiable as to Carcinogenicity in Humans
NTP (National Toxicology Program)
Known - Known Carcinogen
OSHA (Occupational Safety and Health Administration of the US Department of Labor)
X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity Toxic to aquatic life.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Ethyl alcohol	No data available	96h LC50: 12.0 - 16.0 mL/L (Oncorhynchus mykiss) 96h LC50: 13400 - 15100 mg/L (Pimephales promelas) 96h LC50: > 100 mg/L (Pimephales promelas)	EC50 = 34634 mg/L 30 min EC50 = 35470 mg/L 5 min	48h LC50: 9268 - 14221 mg/L (Daphnia magna) 48h EC50: = 2 mg/L (Daphnia magna)
Glycerin	No data available	96h LC50: 51 - 57 mL/L (Oncorhynchus mykiss)	No data available	No data available
Carbomer	No data available	96h LC50: = 580 mg/L (Lepomis macrochirus)	No data available	No data available
Diisopropylamine	96h EC50: = 20 mg/L (Pseudokirchneriella subcapitata)	96h LC50: 150 - 223 mg/L (Brachydanio rerio) 96h LC50: 420 - 560 mg/L (Oryzias latipes) 96h LC50: = 1000 mg/L (Poecilia reticulata) 96h LC50: = 37 mg/L (Oncorhynchus mykiss)	No data available	No data available
tert-Butyl alcohol	72h EC50: > 1000 mg/L (Desmodesmus subspicatus)	96h LC50: 6130 - 6700 mg/L (Pimephales promelas)	EC50 > 10000 mg/L 17 h	48h EC50: 4607 - 6577 mg/L (Daphnia magna) 48h EC50: = 933 mg/L (Daphnia magna)
Isopropyl myristate	72h EC50: > 100 mg/L (Desmodesmus subspicatus)	96h LC50: = 8400 mg/L (Brachydanio rerio)	No data available	48h EC50: = 100 mg/L (Daphnia magna)
Tocopheryl acetate	No data available	96h LC50: > 100 mg/L (Oncorhynchus mykiss)	No data available	No data available
Isopropylamine	96h EC50: = 1.2 mg/L (Desmodesmus	96h LC50: = 310 mg/L (Pimephales promelas)	EC50 = 99 mg/L 17 h	48h EC50: = 20.8 mg/L (Daphnia magna)

	subspicatus) 72h EC50: = 4.13 mg/L (Desmodesmus subspicatus) 96h EC50: = 62.5 mg/L (Pseudokirchneriella subcapitata)			
Isopropyl alcohol	72h EC50: > 1000 mg/L (Desmodesmus subspicatus) 96h EC50: > 1000 mg/L (Desmodesmus subspicatus)	96h LC50: = 11130 mg/L (Pimephales promelas) 96h LC50: = 9640 mg/L (Pimephales promelas) 96h LC50: > 1400000 µg/L (Lepomis macrochirus)	No data available	48h EC50: = 13299 mg/L (Daphnia magna)
Acetone	No data available	96h LC50: 4.74 - 6.33 mL/L (Oncorhynchus mykiss) 96h LC50: 6210 - 8120 mg/L (Pimephales promelas) 96h LC50: = 8300 mg/L (Lepomis macrochirus)	EC50 = 14500 mg/L 15 min	48h EC50: 10294 - 17704 mg/L (Daphnia magna) 48h EC50: 12600 - 12700 mg/L (Daphnia magna)

Persistence and Degradability No information available.

Bioaccumulation

Component Information

Chemical name	Partition coefficient
Ethyl alcohol	-0.32
Glycerin	-1.76
tert-Butyl alcohol	0.35
Isopropyl myristate	6
Isopropylamine	0.26
Isopropyl alcohol	0.05
Acetone	-0.24

Mobility No information available.

Other adverse effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste treatment methods

Waste from residues/unused products Should not be released into the environment. Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Empty containers pose a potential fire and explosion hazard. Do not cut, puncture of weld containers.

US EPA Waste Number D001

California Waste Codes 311

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical name	California Hazardous Waste
Ethyl alcohol 64-17-5	Toxic Ignitable
Isopropylamine 75-31-0	Toxic Ignitable
Isopropyl alcohol 67-63-0	Toxic Ignitable
Acetone 67-64-1	Ignitable

14. TRANSPORT INFORMATION

DOT

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTIONS
Hazard Class	3
Packing Group	III
Description	UN1170, ETHANOL SOLUTIONS, 3, III, LTD QTY
Emergency Response Guide Number	127

TDG

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	III
Description	UN1170, ETHANOL SOLUTION, 3, III, LTD QTY

MEX

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	III
Description	UN1170, ETHANOL SOLUTION, 3, III

ICAO

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	III
Description	UN1170, ETHANOL SOLUTION, 3, III

IATA

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	III
ERG Code	3L
Description	UN1170, ETHANOL SOLUTION, 3, III

IMDG/IMO

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	III
EmS-No.	F-E, S-D
Description	UN1170, ETHANOL SOLUTION, 3, III, (22°C C.C.)

RID

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	III
Classification code	F1
Description	UN1170, ETHANOL SOLUTION, 3, III
ADR/RID-Labels	3

ADR

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	III
Classification code	F1
Tunnel restriction code	(D/E)
Description	UN1170, ETHANOL SOLUTION, 3, III, (D/E)

ADN

UN-No.	UN1170
Proper Shipping Name	ETHANOL SOLUTION
Hazard Class	3
Packing Group	III
Classification code	F1
Special Provisions	144, 601
Description	UN1170, ETHANOL SOLUTION, 3, III
Hazard Labels	3
Limited Quantity	5 L
Ventilation	VE01

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA	Contact supplier for inventory compliance status.
DSL/NDSL	Contact supplier for inventory compliance status.
EINECS/ELINCS	Contact supplier for inventory compliance status.
ENCS	Contact supplier for inventory compliance status.
KECL	Contact supplier for inventory compliance status.
PICCS	Contact supplier for inventory compliance status.
AICS	Contact supplier for inventory compliance status.

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances

AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No	Weight-%	SARA 313 - Threshold Values %
tert-Butyl alcohol - 75-65-0	75-65-0	0.07088	1.0
Isopropyl alcohol - 67-63-0	67-63-0	0.000096	1.0

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Carbomer 9003-01-4		X		

CERCLA

This material, as supplied, does not contain any substances regulated as hazardous substances under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302) or the Superfund Amendments and Reauthorization Act (SARA) (40 CFR 355). There may be specific reporting requirements at the local, regional, or state level pertaining to releases of this material

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Acetone 67-64-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical name	California Proposition 65
Ethyl alcohol - 64-17-5	Carcinogen Developmental

U.S. State Right-to-Know Regulations

.

Chemical name	New Jersey	Massachusetts	Pennsylvania	Rhode Island	Illinois
Ethyl alcohol 64-17-5	X	X	X		X
Glycerin 56-81-5	X	X	X	X	
Carbomer 9003-01-4	X				
Diisopropylamine	X	X	X		

108-18-9					
tert-Butyl alcohol 75-65-0	X	X	X	X	
Isopropylamine 75-31-0	X	X	X		
Isopropyl alcohol 67-63-0	X	X	X	X	
Acetone 67-64-1	X	X	X	X	

16. OTHER INFORMATION

NFPA	**Health hazards** 1	**Flammability** 3	**Instability** 0	**Physical and Chemical Properties** -
HMIS	**Health hazards** 1	**Flammability** 3	**Physical hazards** 0	**Personal Protection** X

Prepared By

Product Stewardship
23 British American Blvd.
Latham, NY 12110
1-800-572-6501

Issuing Date 20-Jul-2021

Revision Date 10-Nov-2020

Revision Note No information available

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet